


# Specifications



MODELS	SLA™-5		SLA™-10		SLA™-15		SLA™-20		SLA™-25	
	Metric	US	Metric	US	Metric	US	Metric	US	Metric	US
<b>Working height:</b>										
STANDARD forks - down	1.49 m	4 ft 10.5 in	2.97 m	9 ft 9 in	4.46 m	14 ft 7.5 in	5.94 m	19 ft 6 in	7.42 m	24 ft 4 in
STANDARD forks - up	2.00 m	6 ft 7 in	3.49 m	11 ft 5.5 in	4.98 m	16 ft 4 in	6.46 m	21 ft 2.5 in	7.94 m	26 ft 0.5 in
adjustable forks - down	1.49 m	4 ft 10.5 in	2.97 m	9 ft 9 in	4.46 m	14 ft 7.5 in	5.94 m	19 ft 6 in	7.42 m	24 ft 4 in
adjustable forks - up	2.00 m	6 ft 7 in	3.49 m	11 ft 5.5 in	4.98 m	16 ft 4 in	6.46 m	21 ft 2.5 in	7.94 m	26 ft 0.5 in
flat forks	1.49 m	4 ft 10.5 in	2.97 m	9 ft 9 in	4.46 m	14 ft 7.5 in	—	—	—	—
boom***	1.79 m	5 ft 10.5 in	3.28 m	10 ft 9 in	4.76 m	15 ft 7.5 in	6.25 m	20 ft 6 in	7.42 m	24 ft 4 in
load platform** - forks down	1.49 m	4 ft 10.5 in	2.97 m	9 ft 9 in	4.46 m	14 ft 7.5 in	5.94 m	19 ft 6 in	7.42 m	24 ft 4 in
load platform** - forks up	2.00 m	6 ft 7 in	3.49 m	11 ft 5.5 in	4.98 m	16 ft 4 in	6.46 m	21 ft 2.5 in	7.94 m	26 ft 0.5 in
<b>A</b> Height - stowed	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in	1.99 m	6 ft 6.5 in
<b>B</b> Length - stowed	0.74 m	2 ft 5 in	0.74 m	2 ft 5 in	0.74 m	2 ft 5 in	0.74 m	2 ft 5 in	0.79 m	2 ft 7 in
<b>C</b> Length - operating	1.51 m	4 ft 11.5 in	1.51 m	4 ft 11.5 in	1.88 m	6 ft 2 in	2.08 m	6 ft 10 in	2.08 m	6 ft 10 in
<b>D</b> Width - stowed*	0.80 m	2 ft 7.5 in	0.80 m	2 ft 7.5 in	0.80 m	2 ft 7.5 in	0.80 m	2 ft 7.5 in	0.80 m	2 ft 7.5 in
- with outriggers lowered	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in	1.85 m	6 ft 1 in
<b>Width - straddle base*</b>										
minimum	0.80 m	2 ft 7.5 in	0.80 m	2 ft 7.5 in	0.80 m	2 ft 7.5 in	—	—	—	—
maximum	1.47 m	4 ft 10 in	1.47 m	4 ft 10 in	1.47 m	4 ft 10 in	—	—	—	—
maximum inside	1.27 m	4 ft 2 in	1.27 m	4 ft 2 in	1.27 m	4 ft 2 in	—	—	—	—
<b>E</b> Ground clearance - centre	0.05 m	2 in	0.05 m	2 in	0.05 m	2 in	0.05 m	2 in	0.05 m	2 in
<b>F</b> Load height minimum	0.15 m	6 in	0.15 m	6 in	0.15 m	6 in	0.15 m	6 in	0.15 m	6 in

## PRODUCTIVITY

	Metric	US	Metric	US	Metric	US	Metric	US	Metric	US
<b>Load capacity:</b>										
18 in (46 cm) load centre	454 kg	1,000 lbs	454 kg	1,000 lbs	363 kg	800 lbs	363 kg	800 lbs	295 kg	650 lbs
24 in (61 cm) load centre	454 kg	1,000 lbs	454 kg	1,000 lbs	363 kg	800 lbs	272 kg	600 lbs	204 kg	450 lbs
42 in (107 cm) load centre	159 kg	350 lbs	181 kg	400 lbs	227 kg	500 lbs	159 kg	350 lbs	113 kg	250 lbs

## POWER

	Metric	US
<b>Average cranks:</b>		
standard winch	27.8 cranks/m	8.5 cranks/ft
two speed winch, high	13.1 cranks/m	4 cranks/ft
two speed winch, low	49.2 cranks/m	15 cranks/ft

## WEIGHT

	Metric	US	Metric	US	Metric	US	Metric	US
Standard	98 kg	215 lbs	118 kg	260 lbs	151 kg	333 lbs	184 kg	405 lbs
Straddle base	117 kg	258 lbs	137 kg	303 lbs	163 kg	360 lbs	—	—

## LOAD HANDLING ATTACHMENTS

MEASUREMENTS	Metric	US	Metric Weight	US Weight
Standard forks (l/w/d)****	69 x 58 x 6 cm	27 x 23 x 2.5 in	18 kg	38.9 lbs
Adjustable forks (l/w/d)****	70 x 30-76 x 6 cm	27.5 x 12-30 x 2.5 in	24 kg	52.5 lbs
Fork extensions detached (each) (l/w/d)****	76 x 5 x 8 cm	30 x 2 x 3 in	2 kg	4.5 lbs
Fork extensions attached (each) (l/w/d)****	64 x 5 x 8 cm	25 x 2 x 3 in	2 kg	4.5 lbs
Flat forks (l/w/d)****	81 x 41-79 x 3.8 cm	32 x 16-31 x 1.5 in	36 kg	80.1 lbs
Boom (l/w/d)****	46-107 x 4 x 16.5 cm	18-42 x 1.5 x 6.5 in	18 kg	39.9 lbs
Pipe cradle (l/w/d)****/*****	69 x 61 x 15.2 cm	27 x 24 x 6 in	4.5 kg	10 lbs
Load platform (l/w/d)****	70 x 58 x 7 cm	27.5 x 23 x 2.75 in	14 kg	31.5 lbs

\* Outside dimensions.  
 \*\* For use with standard and adjustable forks only.  
 \*\*\* Measured from ground to bottom of shackle.  
 \*\*\*\* Length/width/depth.  
 \*\*\*\*\* Handles round objects up to 76 cm (30 in) in diameter.

## Features

### STANDARD FEATURES

#### MEASUREMENTS

##### SLA™-5

- 2.00 m (6 ft 7 in) maximum working height
- Up to 454 kg (1,000 lbs) load capacity

##### SLA™-10

- 3.49 m (11 ft 5.5 in) maximum working height
- Up to 454 kg (1,000 lbs) load capacity

##### SLA™-15

- 4.98 m (16 ft 4 in) maximum working height
- Up to 363 kg (800 lbs) load capacity

##### SLA™-20

- 6.46 m (21 ft 2.5 in) maximum working height
- Up to 363 kg (800 lbs) load capacity

##### SLA™-25

- 7.94 m (26 ft 0.5 in) maximum working height
- Up to 295 kg (650 lbs) load capacity

#### PRODUCTIVITY

- Heavy-duty design
- Patented telescoping mast system
- Captive stabiliser set (standard on SLA™-20, -25)
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Manoeuvrable 10 cm (4 in) front casters and 13 cm (5 in) rear casters, with 4-way swivel locks and side brakes, are standard
- Compact design, legs fold up for easy storage
- Roller wheels allow easy transport in stowed position
- Easy to load and unload on or off a vehicle for transport
- Hold-down bar secures mast assembly during transport
- Standard base

#### POWER

- One speed manual winch

### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Standard forks
- Adjustable forks
- Fork extensions
- Flat forks
- Boom
- Pipe cradle
- Load platform
- Captive stabiliser set (option on SLA™-5, -10, 15)
- Rear transport wheel assembly
- Straddle base (SLA™-5, -10, -15)

#### POWER OPTIONS

- Two speed manual winch



### Genie Australia – Toll free number 1800 788 633

**Brisbane (Head Office)**  
33 Kimberley Street  
Darra QLD 4076

**Sydney**  
74 Glendenning Road  
Glendenning NSW 2761

**Melbourne**  
374 Hammond Road  
Dandenong VIC 3175

**Perth**  
83 Bannister Road  
Canning Vale WA 6155

### Genie United States Distributed by:

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington  
98073-9730

Effective Date: April, 2009. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie and Superlift Advantage are Registered Trademarks of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. © 2009 Terex Corporation.

SLA-10, SLA-15, SLA-20, SLA-25 090327 Ver1

[www.genieindustries.com](http://www.genieindustries.com)