


# Specifications



| MODELS                             | SLA™-5 |              | SLA™-10 |              | SLA™-15 |              | SLA™-20 |              | SLA™-25 |              |
|------------------------------------|--------|--------------|---------|--------------|---------|--------------|---------|--------------|---------|--------------|
|                                    | Metric | US           | Metric  | US           | Metric  | US           | Metric  | US           | Metric  | US           |
| <b>Working height:</b>             |        |              |         |              |         |              |         |              |         |              |
| STANDARD forks - down              | 1.49 m | 4 ft 10.5 in | 2.97 m  | 9 ft 9 in    | 4.46 m  | 14 ft 7.5 in | 5.94 m  | 19 ft 6 in   | 7.42 m  | 24 ft 4 in   |
| STANDARD forks - up                | 2.00 m | 6 ft 7 in    | 3.49 m  | 11 ft 5.5 in | 4.98 m  | 16 ft 4 in   | 6.46 m  | 21 ft 2.5 in | 7.94 m  | 26 ft 0.5 in |
| adjustable forks - down            | 1.49 m | 4 ft 10.5 in | 2.97 m  | 9 ft 9 in    | 4.46 m  | 14 ft 7.5 in | 5.94 m  | 19 ft 6 in   | 7.42 m  | 24 ft 4 in   |
| adjustable forks - up              | 2.00 m | 6 ft 7 in    | 3.49 m  | 11 ft 5.5 in | 4.98 m  | 16 ft 4 in   | 6.46 m  | 21 ft 2.5 in | 7.94 m  | 26 ft 0.5 in |
| flat forks                         | 1.49 m | 4 ft 10.5 in | 2.97 m  | 9 ft 9 in    | 4.46 m  | 14 ft 7.5 in | —       | —            | —       | —            |
| boom***                            | 1.79 m | 5 ft 10.5 in | 3.28 m  | 10 ft 9 in   | 4.76 m  | 15 ft 7.5 in | 6.25 m  | 20 ft 6 in   | 7.42 m  | 24 ft 4 in   |
| load platform** - forks down       | 1.49 m | 4 ft 10.5 in | 2.97 m  | 9 ft 9 in    | 4.46 m  | 14 ft 7.5 in | 5.94 m  | 19 ft 6 in   | 7.42 m  | 24 ft 4 in   |
| load platform** - forks up         | 2.00 m | 6 ft 7 in    | 3.49 m  | 11 ft 5.5 in | 4.98 m  | 16 ft 4 in   | 6.46 m  | 21 ft 2.5 in | 7.94 m  | 26 ft 0.5 in |
| <b>A</b> Height - stowed           | 1.99 m | 6 ft 6.5 in  | 1.99 m  | 6 ft 6.5 in  | 1.99 m  | 6 ft 6.5 in  | 1.99 m  | 6 ft 6.5 in  | 1.99 m  | 6 ft 6.5 in  |
| <b>B</b> Length - stowed           | 0.74 m | 2 ft 5 in    | 0.74 m  | 2 ft 5 in    | 0.74 m  | 2 ft 5 in    | 0.74 m  | 2 ft 5 in    | 0.79 m  | 2 ft 7 in    |
| <b>C</b> Length - operating        | 1.51 m | 4 ft 11.5 in | 1.51 m  | 4 ft 11.5 in | 1.88 m  | 6 ft 2 in    | 2.08 m  | 6 ft 10 in   | 2.08 m  | 6 ft 10 in   |
| <b>D</b> Width - stowed*           | 0.80 m | 2 ft 7.5 in  | 0.80 m  | 2 ft 7.5 in  | 0.80 m  | 2 ft 7.5 in  | 0.80 m  | 2 ft 7.5 in  | 0.80 m  | 2 ft 7.5 in  |
| - with outriggers lowered          | 1.85 m | 6 ft 1 in    | 1.85 m  | 6 ft 1 in    | 1.85 m  | 6 ft 1 in    | 1.85 m  | 6 ft 1 in    | 1.85 m  | 6 ft 1 in    |
| <b>Width - straddle base*</b>      |        |              |         |              |         |              |         |              |         |              |
| minimum                            | 0.80 m | 2 ft 7.5 in  | 0.80 m  | 2 ft 7.5 in  | 0.80 m  | 2 ft 7.5 in  | —       | —            | —       | —            |
| maximum                            | 1.47 m | 4 ft 10 in   | 1.47 m  | 4 ft 10 in   | 1.47 m  | 4 ft 10 in   | —       | —            | —       | —            |
| maximum inside                     | 1.27 m | 4 ft 2 in    | 1.27 m  | 4 ft 2 in    | 1.27 m  | 4 ft 2 in    | —       | —            | —       | —            |
| <b>E</b> Ground clearance - centre | 0.05 m | 2 in         | 0.05 m  | 2 in         | 0.05 m  | 2 in         | 0.05 m  | 2 in         | 0.05 m  | 2 in         |
| <b>F</b> Load height minimum       | 0.15 m | 6 in         | 0.15 m  | 6 in         | 0.15 m  | 6 in         | 0.15 m  | 6 in         | 0.15 m  | 6 in         |

| <b>PRODUCTIVITY</b>        |        |           |        |           |        |         |        |         |        |         |
|----------------------------|--------|-----------|--------|-----------|--------|---------|--------|---------|--------|---------|
| <b>Load capacity:</b>      |        |           |        |           |        |         |        |         |        |         |
| 18 in (46 cm) load centre  | 454 kg | 1,000 lbs | 454 kg | 1,000 lbs | 363 kg | 800 lbs | 363 kg | 800 lbs | 295 kg | 650 lbs |
| 24 in (61 cm) load centre  | 454 kg | 1,000 lbs | 454 kg | 1,000 lbs | 363 kg | 800 lbs | 272 kg | 600 lbs | 204 kg | 450 lbs |
| 42 in (107 cm) load centre | 159 kg | 350 lbs   | 181 kg | 400 lbs   | 227 kg | 500 lbs | 159 kg | 350 lbs | 113 kg | 250 lbs |

|                        | <b>Metric</b> |  | <b>US</b>     |  |
|------------------------|---------------|--|---------------|--|
| <b>Average cranks:</b> |               |  |               |  |
| standard winch         | 27.8 cranks/m |  | 8.5 cranks/ft |  |
| two speed winch, high  | 13.1 cranks/m |  | 4 cranks/ft   |  |
| two speed winch, low   | 49.2 cranks/m |  | 15 cranks/ft  |  |

| <b>WEIGHT</b> |        |         |        |         |        |         |        |         |        |         |
|---------------|--------|---------|--------|---------|--------|---------|--------|---------|--------|---------|
| Standard      | 98 kg  | 215 lbs | 118 kg | 260 lbs | 151 kg | 333 lbs | 184 kg | 405 lbs | 204 kg | 450 lbs |
| Straddle base | 117 kg | 258 lbs | 137 kg | 303 lbs | 163 kg | 360 lbs | —      | —       | —      | —       |

| <b>LOAD HANDLING ATTACHMENTS</b>            |                      |  |                       |  |                                |          |
|---|----------------------|--|-----------------------|--|--------------------------------|----------|
| MEASUREMENTS                                | <b>Metric</b>        |  | <b>US</b>             |  | <b>Metric Weight US Weight</b> |          |
| Standard forks (l/w/d)****                  | 69 x 58 x 6 cm       |  | 27 x 23 x 2.5 in      |  | 18 kg                          | 38.9 lbs |
| Adjustable forks (l/w/d)****                | 70 x 30-76 x 6 cm    |  | 27.5 x 12-30 x 2.5 in |  | 24 kg                          | 52.5 lbs |
| Fork extensions detached (each) (l/w/d)**** | 76 x 5 x 8 cm        |  | 30 x 2 x 3 in         |  | 2 kg                           | 4.5 lbs  |
| Fork extensions attached (each) (l/w/d)**** | 64 x 5 x 8 cm        |  | 25 x 2 x 3 in         |  | 2 kg                           | 4.5 lbs  |
| Flat forks (l/w/d)****                      | 81 x 41-79 x 3.8 cm  |  | 32 x 16-31 x 1.5 in   |  | 36 kg                          | 80.1 lbs |
| Boom (l/w/d)****                            | 46-107 x 4 x 16.5 cm |  | 18-42 x 1.5 x 6.5 in  |  | 18 kg                          | 39.9 lbs |
| Pipe cradle (l/w/d)****/*****               | 69 x 61 x 15.2 cm    |  | 27 x 24 x 6 in        |  | 4.5 kg                         | 10 lbs   |
| Load platform (l/w/d)****                   | 70 x 58 x 7 cm       |  | 27.5 x 23 x 2.75 in   |  | 14 kg                          | 31.5 lbs |

\* Outside dimensions.  
 \*\* For use with standard and adjustable forks only.  
 \*\*\* Measured from ground to bottom of shackle.  
 \*\*\*\* Length/width/depth.  
 \*\*\*\*\* Handles round objects up to 76 cm (30 in) in diameter.

## Features

### STANDARD FEATURES

#### MEASUREMENTS

##### SLA™-5

- 2.00 m (6 ft 7 in) maximum working height
- Up to 454 kg (1,000 lbs) load capacity

##### SLA™-10

- 3.49 m (11 ft 5.5 in) maximum working height
- Up to 454 kg (1,000 lbs) load capacity

##### SLA™-15

- 4.98 m (16 ft 4 in) maximum working height
- Up to 363 kg (800 lbs) load capacity

##### SLA™-20

- 6.46 m (21 ft 2.5 in) maximum working height
- Up to 363 kg (800 lbs) load capacity

##### SLA™-25

- 7.94 m (26 ft 0.5 in) maximum working height
- Up to 295 kg (650 lbs) load capacity

#### PRODUCTIVITY

- Heavy-duty design
- Patented telescoping mast system
- Captive stabiliser set (standard on SLA™-20, -25)
- Rolls easily through single door in upright position
- Quick set up requires no tools
- Interchangeable load handling attachments
- Manoeuvrable 10 cm (4 in) front casters and 13 cm (5 in) rear casters, with 4-way swivel locks and side brakes, are standard
- Compact design, legs fold up for easy storage
- Roller wheels allow easy transport in stowed position
- Easy to load and unload on or off a vehicle for transport
- Hold-down bar secures mast assembly during transport
- Standard base

#### POWER

- One speed manual winch

### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Standard forks
- Adjustable forks
- Fork extensions
- Flat forks
- Boom
- Pipe cradle
- Load platform
- Captive stabiliser set (option on SLA™-5, -10, 15)
- Rear transport wheel assembly
- Straddle base (SLA™-5, -10, -15)

#### POWER OPTIONS

- Two speed manual winch



### Genie Australia – Toll free number 1800 788 633

**Brisbane (Head Office)**  
33 Kimberley Street  
Darra QLD 4076

**Sydney**  
74 Glendenning Road  
Glendenning NSW 2761

**Melbourne**  
374 Hammond Road  
Dandenong VIC 3175

**Perth**  
83 Bannister Road  
Canning Vale WA 6155

### Genie United States Distributed by:

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington  
98073-9730

Effective Date: April, 2009. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie and Superlift Advantage are Registered Trademarks of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. © 2009 Terex Corporation.

SLA-10, SLA-15, SLA-20, SLA-25 090327 Ver1

[www.genieindustries.com](http://www.genieindustries.com)