10MSP MOBILE STOCK PICKER



Performance

Platform Height	3.05 m
Working Height	5.05 m
Drive Height	Max. Platform Height
Stowed Height	145 cm
Platform Entry Height	35 cm
Platform Size (W x L)	50 x 69 cm
Overall Vehicle Length	
Chassis Length	156 cm
Overall Vehicle Width	
Chassis Width (with guide rollers)	89 cm
Chassis Width (with bumper)	83 cm
Chassis Width (without bumper)	75 cm
Gross Vehicle Weight	499 kg
Capacity	
Platform	160 kg
Carry Deck	115 kg
Powered Material Tray	90 kg
Max. Drive Speed	
Platform Lowered	8.0 km/h
Platform Elevated	0.8 km/h
Turning Radius	Zero
Gradeability	15%
Underclearance	5 cm

Standard Specifications

Power Source

Batteries Battery Charger	4 x 6V 210 amp-hr Maintenance-free (AGM) 25 Amp Automatic
Drive System	4 Brush Direct Electric (Planetary Gear)
Tyres	

Rear Drive & Steer Wheels Front Caster Wheels 32 x 10 cm (Non-marking) 20 x 6 cm (Non-marking)



Standard Features

- Heavy-duty Planetary Gear Drive Motors
- Simultaneous Lift and Drive Capability
- Point & Go[®] One-hand Drive and Steer System
- Proportional Drive
- Automatic Five-hour Battery Charger
- Battery Discharge Indicators —
- Platform and Base • Lubrication-free Anodized Aluminum
- Mast Sections
- Maintenance-free Mast Guide System
- Strobe Lights Front and RearMotion Alarm
- Slope Cut-out Control Interlock 1.5°

Accessories & Options

- Programmable 4-Digit Security Lock
- Fluorescent Light Tube Caddy
- Object Sensing Pad

- Stand-on Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- Self-closing Self-locking Platform Gate
- Powered Adjustable Height Material Tray
- Non-marking Tyre Material
- Lanyard Attachment Anchor Point
- Hourmeter
- Horn
- Guide Roller System
- Transportation Tie DownsSide and Front Bumpers
- Side and Front Bumpe
- Rubber Floor Mat

Scanner Pocket

Cargo Strap



JLG Industries (Australia)

358 Park Road Regents Park, NSW 2143 Telephone 02 8718 6300 Fax 02 8718 6377 www.jlg.com.au

The JLG "1 & 5" Warranty

JLG Industries, Inc., backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.